



Circulating Self Priming Horizontal End Suction Centrifugal Pump Chemical Transfer Pump

Our Product Introduction

Basic Information

- Place of Origin: Sichuan, China
- Brand Name: horizontal-slurrypump.com
- Certification: ISO9001
- Model Number: OEM
- Minimum Order Quantity: 1 set
- Price: USD 500-5000/set
- Packaging Details: free fumigation export wooden box packaging
- Delivery Time: 25 working days after receiveing advance payment
- Payment Terms: L/C, D/A, D/P, T/T, Western Union, MoneyGram, Paypal
- Supply Ability: 300 sets per month



Product Specification

- Theory: Centrifugal Pump
- Max Flow: 1000m3/h
- Max Head: 120m
- Pressure: 1.6MPa
- Temperature: -50-130
- Color: Customized
- Standard Or Nonstandard: Standard
- Name: High Efficiency Centrifugal Single Stage Horizontal Axially Split Casting Chemical Pump
- Structure: Single-stage Pump
- Frequency: 50hz Or 60hz Are All Available
- Highlight: horizontal high pressure centrifugal pump

for more products please visit us on horizontal-slurrypump.com

Product Description

Circulating Self Priming Horizontal End Suction Centrifugal Pumps Chemical Transfer Pump

Main Feature

- 1) simple pump structure, simple installation and convenient maintenance.
- 2) 100% copper coil is adopted for the motor to ensure the service life.
- 3) wide range of application, which can be widely used in living, industrial, chemical and other fields.
- 4) the explosion-proof motor can be customized to protect your safety.

Details



Mechanical Seal

Character : Fluoropolymer alloy spring is 304 stainless steel material, with high temperature resistance, acid and alkali resistance, corrosion resistance, wear resistance and other characteristics, especially suitable for all kinds of bad environment

precision impeller ring

Character : We use more professional measuring tools to closely measure the bearing joints to ensure the accuracy to international standards.



The clearance between the impeller and the pump body less than 0.03 mm



The Motor Coil

Character : We use pure copper core wire with 100% purity up to standard as stator winding, which effectively ensures less heat generation, higher operating efficiency and longer service life of click. There is no obvious vibration when carrying over the flat ground. Slow warming, more energy efficient.

Pump Body


Character : Good thick pump body casting, is the quality assurance of water pump, guaranteed wear-resistant and durable performance, service life can reach more than 10 years; Low noise, low vibration, easy installation.



Performance Data

Structure	Single Stage
Head	10-90m
Flow	8-800 m3/h
Speed	980-2950 r/min
Power	1.1-160 kw
Efficiency	18%-85%
NPSH	1.4-4.5 m
Standard	ISO9001

Structure



*1	Locking screw	*8	Vice impeller chamber	15	Front bearing cap	22	Oil pan	*29	Sleeve
2	Gasket	9	O-ring	*16	Front bearing	23	Adjustment nut	30	Water seal ring
*3	Impeller nut	*10	Vice impeller	17	Bearing body	24	Adjustment screw	31	Filler
4	O-ring	*11	Packing chamber	18	Bearing bracket	25	Bearing body bracket	32	O-ring
*5	Impeller	12	O-ring	*19	Rear bearing	*26	axis	*33	keys
*6	Pump body	13	Rinse water nozzle	20	Rear bearing cover	27	Shield cover		
7	O-ring	14	Water retaining plate	21	Key	28	Packing gland		

Product Picture



Technical parameter Sheet

Model	Flow (m³/h)	Head (m)	Speed (r/min)	Maximum efficiency (%)	NPSH (NPSHr)m
40WD-250	8-30	15-28	1450	39	1.5
40WD-310	8-30	23-38	1450	37	1.7
40WD-350	8-30	35-50	1450	35	1.7
50WD-250	30-50	15-28	1450	40	1.4
50WD-310	30-60	25-38	1450	45	1.5

50WD-350	30-60	35-50	1450	43	1.8
50WD-400	30-60	50-75	1450	35	1.8
65WD-250	50-80	15-28	1450	48	1.8
65WD-310	50-100	25-38	1450	50	2.2
65WD-350	50-100	35-50	1450	55	2.2
65WD-400	50-100	45-75	1450	53	2.7
65WD-450	50-100	70-90	1450	52	2.8
80WD-250	70-140	15-25	1450	61	2.5
80WD-310	70-140	25-38	1450	62	2.5
80WD-350	70-160	35-50	1450	63	2.8
80WD-400	70-160	50-70	1450	62	2.8
80WD-450	70-160	70-90	1450	60	2.8
100WD-310	100-220	20-35	1450	57	2.8
100WD-350	100-220	35-48	1450	60	2.8
100WD-400	100-220	40-65	1450	68	2.8
125WD-310	120-250	18-33	1450	62	3
125WD-350	120-290	35-48	1450	62	3
125WD-400	140-300	35-60	1450	65	3
150WD-310	200-400	18-33	1450	64	3.5
150WD-350	200-400	25-45	1450	65	3.5
150WD-400	200-400	40-55	1450	67	3.5
200WD-350	300-600	28-38	1450	67	4
200WD-430	300-650	50-64	1450	70	4
250WD-430	400-800	50-60	1450	70	4.5

Service

Any inquires will be replied within 8 working hours.

Professional centrifugal pump manufacturer, welcome to visit our website (on-line store) and factory.

Customized design is available, OEM and ODM are welcomed.

High quality, reasonable & competitive price.


Payment: we usual accept payment by T/T, L/C and western union.

After-sale service: all centrifugal pumps will have been strictly quality checked in house before packing.

All centrifugal pumps will be well packed as request before shipping.

 **ROMAN** Beijing Silk Road Enterprise Management Services Co.,LTD

 86-17773109286

 jeffreyth@slurypump.com

 horizontal-slurypump.com

Floor 5, 2nd Building, Zhonglu Industrial Zone, Shenzhen City, Guangdong Province China (Mainland)